



Speedshine® specifications



Models	1700HD	2000HD
Brush RPM		175 rpm
Motor volts		120 volts
Motor hp		1.5 hp / 1.12 kW
Motor amps		12 A
Motor type	AC, 66 frame, heavy duty, circuit breaker protected; triple planetary; precision gear box, 10:1 gear ratio	
Motor watts	1100 watts	
Solution Delivery System (optional)		
Tank volume	3 gal / 11.36 L	
Nominal solution flow rate	0.1 gpm / 0.38 L / min	
Coverage rate per tank	1000 sq ft / 92.9 sq m per tank	1500 sq ft / 135.35 sq m per tank
Productivity		
Max. coverage per hour	2000 ft ² / 185.8 m ²	3000 ft ² / 278.7 m ²
Power System		
Power cord length	50 ft / 15.24 m	
Power cord description	14 gauge, 3-wire, SJT	
Dimensions / Weight / Sound level		
Height	48 in / 1219 mm	48 in / 1219 mm
Length	22.75 in / 578 mm	23.5 in / 597 mm
Weight	97 lb / 44 kg	100 lb / 45.36 kg
Width	17 in / 403 mm	20 in / 510 mm
Sound level (operator's ear)	60 dBa	60 dBa
Warranty	3 years/2500 hrs on parts and labor. 10 years on rotationally-molded polyethylene parts.	