



SS Rider - DAILY OPERATOR CHECKLIST

PRE-OPERATION CHECKLIST

- ☐ Check the battery fluid and charge level
- ☐ Check the tank cover seals for damage and wear
- ☐ Clean the vacuum fan inlet filter
- ☐ Check the condition of the scrubbing brushes
(Remove any string, banding, plastic wrap, or other debris wrapped around them)
- ☐ Check the squeegees for damage, wear and for deflection adjustment
- ☐ Check the vacuum hose for debris or blockage
- ☐ Drain and clean the recovery tank
- ☐ Check the brakes and steering for proper operation
- ☐ FaST Scrubbing: Check the optional FaST—PAK concentrate agent level
- ☐ FaST Scrubbing: Ensure that all conventional cleaning agents are drained and rinsed from the solution tank
- ☐ FaST Scrubbing: Ensure that the solution tank is filled with **clear cool water only**
- ☐ Check the service records to determine maintenance requirements

POST-OPERATIONAL CHECKLIST

- ☐ Clean the solution and recovery tanks
- ☐ Clean the vacuum fan inlet filter
- ☐ Check the scrub head and brushes for banding, plastic wrap and twine
- ☐ Check the squeegees for damage or wear
- ☐ Check the vacuum hoses for debris or blockage
- ☐ Check the battery charge levels to determine if the batteries need charging
- ☐ Check the fluid level of all battery cells and place the machine on the charger, if needed

List below any problems that occurred during operation.

OPERATOR _____ **DATE** _____

SUPERVISOR _____ **DATE** _____

¹ E:\Techtr\Machines\SS Rider\SS Rider-Opck.doc